

Bluetooth Serial Adapter, Promi-SD101/202/205



Features

- * Provides transparent RS232 serial cable replacement.
- * Supports Bluetooth Serial Port Profile and Generic Access Profile.
- * Interoperability with PDA, laptops etc.
- * Working distance:
Promi-SD101: Class 2, Nom. 30 meters, up to 300m using patch antenna
Promi-SD202: Class 1, Nom. 100 meters, up to 1000m using patch antenna
Promi-SD205: Class 1, Nom. 100 meters, up to 1000m using patch antenna
- * Easy to use Windows configuration tool available.
- * No external drivers required.

Promi-SD Series is a wireless serial adapter product line based on Bluetooth technology. Promi-SD Series enables RS232-based serial devices to communicate wirelessly throughout the range of 30m ~ 300m (Promi-SD101-Class 2) or 100m ~ 1000m (Promi-SD202/205-Class 1).


Users may configure the Promi-SD Series by using easy-to-use Windows-based utility software or by using standard AT command set.

Using the Promi-SD205's DIP-switch, user can simply configure Baud Rate and Hardware Flow Control settings of the Promi-SD205. Pairing-button enables 2 Promi-SD205's to connect automatically.

Their various power supply configurations allow users to choose which options suits them best, i.e. Power by DC power cable, Power by external DC adapter, Power by USB power cable, Power by pin 9 of DB9 connector.

Panel Layout


Promi-SD101/202



Typical application areas of the Promi-SD Series include:

- * RS232 cable replacement
- * Wireless Factory monitoring
- * Truck/Bus monitoring system
- * PLC programming
- * Car Diagnostics
- * Wireless Printing
- * Wireless POS system
- * Wireless logistics
- * Wireless machine(healthcare/industrial) monitoring

Promi-SD205



Bluetooth Serial Adapter, Promi-SD101/202/205

Specifications

Serial Interface:

- * Promi-SD101:
 - RS232, Female DB9, 1200 to 115 Kbps
 - CTS/RTS flow control: Default
 - DTR/DSR is not available
- * Promi-SD202/205:
 - RS232, Female DB9, 1200 to 230 Kbps
 - CTS/RTS flow control: Default
 - DTR/DSR for loop-back & full transfer

Bluetooth Interface:

- * Promi-SD101 :
 - Bluetooth v1.1
 - Class 2
 - Level - 4 dBm
 - Protocols - RFCOMM, L2CAP, SDP
 - Profiles - General Access Profile, Serial Port Profile
 - Working distance
 - Default Antenna - Default Antenna 30 meters
 - Default Antenna - Dipole Antenna 50 meters
 - Dipole Antenna - Dipole Antenna 80 meters
 - Patch Antenna - Dipole Antenna 150 meters
 - Patch Antenna - Patch Antenna 300 meters
- * Promi-SD202/205 :
 - Bluetooth v1.1
 - Class I
 - Level - 18 dBm
 - Protocols - RFCOMM, L2CAP, SDP
 - Profiles - General Access Profile, Serial Port Profile
 - Working distance
 - Default Antenna - Default Antenna 100 meters
 - Default Antenna - Dipole Antenna 150 meters
 - Dipole Antenna - Dipole Antenna 200 meters
 - Patch Antenna - Dipole Antenna 400 meters
 - Patch Antenna - Patch Antenna 1,000 meters

Configuration:

- * PromiWin, PromiWizard
- * Modem AT command set

Diagnostic LED:

- * Promi-SD101/202 :
 - Status and Power LED
- * Promi-SD205 :
 - Power
 - Standby
 - Connect
 - RS232-Tx
 - RS232-Rx

Power:

- * Promi-SD101 :
 - 5V, minimum 150mA
 - nominal power consumption of 35.3mA@9600bps and 40mA@115Kbps speed
- * Promi-SD202/205 :
 - 5V~12V, minimum 150mA
 - nominal power consumption of 40mA@9600bps and 72mA@115Kbps speed
- * Common Power supply options:
 - Power via a standard AC-plug DC-adapter
 - Power via USB power cable
 - Power via DC power cable
 - Power via pin 9 of DB9 connector

Environmental:

- * Operating temperature:
 - 0 c to 50 c
- * Storage temperature:
 - 20 c to 66 c
- * Humidity: 90% Non-condensing

Physical properties:

- * Dimension (L x W x H)
 - 91x 31 x 16 (mm)
 - 3.8 x 1.2 x 0.6 (in.)

Certification:

- * Bluetooth 1.1
- * FCC , CE (Except for Promi-SD 205)

Warranty:

- * 1-year limited warranty

Ordering Information

- SD101** Promi-SD101 Serial-Bluetooth Adapter-Class 2 with internal rechargeable battery
- SD202** Promi-SD202 Serial-Bluetooth Adapter-Class 1
- SD205** Promi-SD205 Serial-Bluetooth Adapter-Class 1-DIP

Single Pack Includes :

- * DPA : Promi-DPA DC power cable for SD series
- * UPA : Promi-UPA USB Power Cable
- * SAT : Promi-SAT Stub Antenna-SMA Male-Left Handed
- * OPA : Promi-OPA External Power Adaptor-International - 4 types: EU, America, UK, Australia or EPA : Promi-EPA External Power Adaptor-220V
- * CD-ROM

10-Unit Bulk Pack Includes :

- * SAT : Promi-SAT Stub Antenna-SMA Male-Left Handed
- * DPA : Promi-DPA DC power cable for SD series

Optional Accessories :

- * UPA : Promi-UPA USB Power Cable
- * OPA : Promi-OPA External Power Adaptor-International - 4 types: EU, America, UK, Australia OR EPA : Promi-EPA External Power Adaptor-220V
- * SPC : Promi-SPC Serial Power Cable + Power Adapter
- * DAT : Promi-DAT Dipole Antenna-SMA Male-Left Handed
- * PAT : Promi-PAT Patch Antenna-SMA R/A Female-Right Handed
- * RFC : Promi-RFC 1m Antenna Extension Cable for all antennas
- * CD-ROM

For more information, please visit us at
<http://www.sena.com>

U.S. / Canada / South America
Tel : +1 (408) 573-7425 Fax: +1 (408) 907-3738

EU / Africa
Tel : +33 (0) 1 53 53 16 29 Fax: +33 (0) 1 70 24 70 90

Asia / Pacific
Tel : +82-2-571-8283 Fax: +82-2-573-7710

Contact us via E-mail
General Information : info@sena.com
Sales & Distribution : sales@sena.com
Technical Support : support@sena.com

SENA
www.sena.com